SHELARAK® M 500





SHELARAK® M 500



Bench top sealer for heavy-duty use, especially in blood processing labs

The bench top sealer, Shelarak[®] M 500, has been designed to meet high standards in blood components precessing: consistent high quality sealing excellent performance after repeated use, safety features and easy use.

EASY USE

- Automatic sealing process (when tube is placed in the slot of Head unit)
- ► LED lights for visual process control
- Tube is easily pulled apart
- Front electrode can be easily removed for cleaning
- Portable, can be used in blood collection camps

SAFETY FEATURES

Splash and touch protected sealing area

CONSISTENT HIGH QUALITY SEALING & EXCELLENT PERFORMANCE

- For all types and size of tubes (up to 5mm outer diameter)
- For sealing (0.5-3 sec) with a sophisticated sensing system to automatically adapt sealing time

TECHNICAL SPECIFICATIONS

Sealing time	0.5-3 sec. Depending on tubing	
RF Output	15W/50Hz max./50Ω/40.68 Mhz	
Input Power	110/230 V∼ -50/60 Hz, SMPS system	
Consumption	50 VA	
Size (W x L x H)	260 x 260 x 140 mm	
Weight KG	4 KG	
In compliance	CE marked	
Design Standard	according to IEC 601-2-2 and IS 7583 safety & design standard	



Authorized Distributor	